

RADIATION TECHNOLOGY



SaphyRAD



Multi-probe contamination monitor

- Embedded alarm & distance control indicator
- Adaptive nuclide library
- Control of small & large areas
- Ergonomic, adapted for use by non-specialists



WWW.BERTIN-INSTRUMENTS.COM

PEO B.V.

info@gotopeo.com www.gotopeo.com

The Netherlands Havenweg 16, 6603 AS Wijchen +31 (0)24 648 86 88

Belgium +32 (0)3 309 32 09

Watermolenstraat 2, B-2910 Essen

CoC 34107894 VAT NL807859151B01 IBAN NL29 RABO 0356 1960 46 **BIC** RABONL2U



SAPHYRAD



Contamination monitor for alpha, beta & gamma radiations

SaphyRAD is a multiprobe handheld device used for the detection of alpha, beta and gamma radioactive contaminations. **Its ergonomic interface and ruggedized design** have been specially developed for use in harsh environment by non radiation specialists, in nuclear and NORM (Naturally Occurring Radioactive Material) industries but also in the medical field.

SaphyRAD's **wide range of contamination probes** include an **embedded distance control indicator**. Combined with its specific algorithm, they ensure a very fast and reactive detection. Depending on the probe, the ess small or large areas, through **direct control or smear test**.

operator can either assess small or large areas, through direct control or smear test.

The integrated radionuclide library of the SaphyRAD can be supplemented by the user with other nuclides, for an adapted contamination control depending on the applications. The SaphyRAD is **also compatible with a large range of existing analog monitoring probes**.

External smart probes for contamination measurement

	AB31	AB100	A/B100	AB170	A/B170	A/BG170
Probes		<	No.			
Surface of detection (cm ²)	31	100		170		
Type of detection	 One measurement channel α +βγ 		 One measurement channel α One channel βγ 	• One measurement channel α +βγ	 One measurement channel α One channel βy 	
Use	Accurate & targeted detection	Large areas screening				

Accessories available: Floor stand (for clearance control), calibration tool (for self-calibration or periodic check up), smear test (for indirect measurement), maintenance software (for settings & firmware upgrade).

Health Physics devices

Discover Bertin Instruments' other products



Versatile multipurpose contamination & survey meter

Technical features

MEASUREMENT MODES Direct Measurement Indirect Measurement Detection Scaler

ALARM MANAGEMENT 2 configurable thresholds

PROFILE MANAGEMENT 3 configurable profiles

DATA STORAGE On SD-Card

6 large buttons designed for use with gloves

RADIOELEMENTS 20 customizable nuclides

DISPLAY 3.5" color LCD display Automatic backlight

<mark>BATTERIES</mark> Li-lon 6.8Ah

AUTONOMY Jp to 45 hours

INTERNATIONAL STANDARD Compliant with IEC60325

DIMENSIONS / WEIGHT 200 x 110 x 50 mm / 650

Bertin Technologies S.A.S • Parc d'Activités du Pas du Lac • 10 bis, avenue Ampère, 78180 Montigny Le Bretonneux, France WWW.BERTIN-INSTRUMENTS.COM RCS: 422 511 204 VERSAILLES | SIREN: 422 511 204

PEO B.V.

info@gotopeo.com www.gotopeo.com The Netherlands Havenweg 16, 6603 AS Wijchen

Havenweg 16, 6603 AS Wijc +31 (0)24 648 86 88

Belgium

Watermolenstraat 2, B-2910 Essen +32 (0)3 309 32 09

CoC 34107894 VAT NL807859151B01 IBAN NL29 RABO 0356 1960 46 BIC RABONL2U

in